

# Dynasytan® F 8815

## Modified fluoroalkyl siloxane, water borne

### Technical data

Properties and test methods	Value	Unit	Method
Density (20 °C)	approx. 1.058	g/cm <sup>3</sup>	DIN 51757
Viscosity (20 °C)	approx. 1.6	mPa.s / cSt	-
Flash point	> 95	°C	DIN EN ISO 2719
Boiling point (1.013 hPa)	97	°C	ASTM D - 1120

### Registrations

#### Dynasytan® F 8815

EINECS/ELINCS (EU):	Yes
AICS (Australia):	No
DSL/NDSL (Canada):	No
PICCS (Philippines):	No
TSCA (USA):	Yes (Spraying is prohibited)
IECS (P.R. China):	Yes
ENCS (Japan):	No
ECL (South Korea):	Yes
REACH (Europe)	Exempted

Dynasytan® F 8815 is a fluoroalkylfunctional water-borne oligosiloxane which acts as a surface modification agent on oxidic, carboxy- and hydroxyfunctional substrates for example ceramic, natural fibers like cotton or leather.

Dynasytan® F 8815 is a yellowish, slightly turbid liquid. The product can be mixed with water to any desired concentration.

### Safety and handling

Before considering the use of Dynasytan® products please read its Safety Data Sheet (SDS) thoroughly for safety and toxicological data as well as for information on proper transportation, storage and use. The Safety Data Sheet is available after registration on our website [www.dynasytan.com](http://www.dynasytan.com) or upon request from your local representative, customer service or from Evonik Resource Efficiency GmbH, Product Safety Department, E-MAIL [sds-hu@evonik.com](mailto:sds-hu@evonik.com).

### Packaging, storage and shelf life

Dynasytan® F 8815 is supplied in 25 or 200 kg drums.

Dynasytan® F 8815 should be protected from freezing and temperatures above 40 °C.

In the original closed container, the shelf life of Dynasytan® F 8815 is min. 12 months from delivery.

## Properties and applications

Dynasylan® F 8815 can be used in a great variety of applications.

### Examples:

- Additive for sol-gel/ hybrid systems
- Modification of paints and varnishes
- Hydrophobation of leather
- Water- and oil-repellent, easy-to-clean treatment of textiles

## Reactivity

Dynasylan® F 8815 is a trifunctional organic compound: The reactive silanol groups can bind chemically to an inorganic substrate. Aminoalkyl-functional substituents provide solubility in water. The fluoroalkyl-functional groups impart an extremely low specific surface energy once the siloxane is homogeneously distributed on the substrate.

Similar coatings with good hydro- and oleophobicity can be obtained with commercially available fluorocarbon compounds. A general advantage of Dynasylan® F 8815 is the ability to create a chemical bond to the substrate system. Subsequent horizontal crosslinking then takes place forming 2- and 3-dimensional networks.

Thus starting from very low concentrations Dynasylan® F 8815 forms chemically, thermally and mechanically stable coatings.

## Processing

Substrate surfaces need to be absolutely clean and degreased before treatment!

Dynasylan® F 8815 can be mixed with water in any proportion. Before using the product must be mixed thoroughly to homogenize it. The exact concentration required may slightly vary upon the desired application. A ready-for-use solution can be stored for several days.

Textiles such as cotton can be dipped in or sprayed with a 5-15 wt.-% aqueous solution of Dynasylan® F 8815. The dipping time which corresponds to the reaction time should be 0.5-10 minutes.

A good hydrophobic effect on leather can be obtained by polishing the Dynasylan® F 8815 on to the material.

A thin polysiloxane coating is formed and its specific properties emerge within a few hours at room temperature. The crosslinking process can be accelerated by heating (80-150 °C). Hydro- and oleophobic properties can be determined by measuring the static contact angle.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

#### **Europe/Middle-East/Africa/RoW**

##### **Evonik Resource Efficiency GmbH**

Business Line Silanes  
Rodenbacher Chaussee 4  
63457 Hanau-Wolfgang  
Germany  
PHONE +49 6181 59 13636  
FAX +49 6181 59 713915  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik (SEA) Pte. Ltd.**

Business Line Silanes  
3 Internatioanl Business Park  
#07-18, Nordic European Centre  
Singapore 609927  
PHONE +65 6809 6576  
FAX +65 6809 6699  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik Japan Co. Ltd**

Business Line Silanes  
12th Floor Monolith Building  
2-3-1, Nishi-Shinjuku-ku  
Tokyo 163-0912  
Japan  
PHONE +81 353 23 7446  
FAX +81 353 23 7397  
dynasytan@evonik.com  
www.dynasytan.com

#### **North America**

##### **Evonik Corporation**

Business Line Silanes  
299 Jefferson Road  
Parsippany, NJ 07054-0677  
USA  
PHONE (TOLL FREE) +1 800 237 67 45  
PHONE +1 973 929 8513  
FAX +1 973 929 8503  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik Specialty Chemicals (Shanghai) Co. Ltd.**

Business Line Silanes  
55, Chungdong Road  
Xinzhuang Industry Park  
Shanghai 201108  
P.R. China  
PHONE +86 21 61191-399  
FAX +86 21 61191-648  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik India Pvt. Ltd.**

Business Line Silanes  
Krislon House  
Saki Vihar Road, Anderi (E)  
Mumbai - 400 072  
India  
PHONE +91 226 7238 809  
FAX +91 226 7238 811  
dynasytan@evonik.com  
www.dynasytan.com

#### **North America**

##### **Silbond Corporation**

9901 Sand Creek Highway  
Weston, MI 49289  
USA  
PHONE +1 517 436 9316  
FAX +1 517 436 3148  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik Korea Ltd.**

Business Line Silanes  
94, Galsan 1-dong  
Bupyeong-gu  
Incheon, 403-081  
Korea  
PHONE +82 2320 4773  
FAX +82 2783 2520  
dynasytan@evonik.com  
www.dynasytan.com

#### **Latin America**

##### **Evonik Brasil Ltda.**

Business Line Silanes  
Alameda Campinas, 579  
01404-000 São Paulo-SP  
Brazil  
PHONE +55 11 3146 4123  
FAX +55 11 3146 4148  
dynasytan@evonik.com  
www.dynasytan.com

#### **Asia / Pacific**

##### **Evonik Taiwan Ltd.**

Business Line Silanes  
Artist Construction Bldg.  
9F, No. 133  
Min Sheng East Road, Sec 3  
Taipei, 105 Taiwan, R.O.C.  
Taiwan 10596  
PHONE +886 227 17 1242  
FAX +886 227 17 2106  
dynasytan@evonik.com  
www.dynasytan.com