

Protectosil® PROFICLEAN PLUS

Graffiti cleaner for Protectosil ANTIGRAFFITI® treated porous mineral surfaces

Technical Data

Properties and test methods	Value	Unit	Method
Density	0,956	g/cm ³	DIN 51757
Smell	lemon like	-	-
pH-value	6,1	-	DIN 53015
Appearance	slightly viscous liquid, yellowish and slightly turbid	-	-
Flash point	> 20	°C	DIN 51755
Boiling point	125	°C	DIN 51751

Registration

Protectosil® PROFICLEAN PLUS

EINECS/ELINCS (EU):	Yes
AICS (Australia):	Yes
DSL/NDSL (Canada):	Yes
PICCS (Philippines):	Yes
TSCA (USA):	Yes
IECSC (P.R. China):	Yes
ENCS (Japan):	Yes
ECL (South Korea):	Yes

Protectosil® PROFICLEAN PLUS is a very effective graffiti cleaner with a lemon like smell.

Protectosil® PROFICLEAN PLUS was particularly designed for cleaning surfaces treated with Protectosil ANTIGRAFFITI®. Spray colors, laquers, felt-tip or ball pen scribbling can be easily removed using Protectosil® PROFICLEAN PLUS.

Safety and Handling

Before considering the use of Protectosil® products please read its Safety Data sheet (SDS) thoroughly for safety and toxicological data as well as for information on proper transportation, storage and use. The Safety Data Sheet is available on our website www.protectosil.com or upon request from your local representative, customer service or from Evonik Operations GmbH, Product Safety Department, E-MAIL sds-hu@evonik.com.

Packaging and Storage

Protectosil® PROFICLEAN PLUS has a shelf life in properly sealed containers of more than one year. The product should be stored at temperatures between 0 °C and 40 °C. Protectosil® PROFICLEAN PLUS is supplied in 25 l and 200 l drums.

Properties and Use

Protectosil® PROFICLEAN PLUS should be homogeneously distributed over the surfaces by using a soft roller or brush (e.g. paint brush). Surfaces should be dry and temperatures should be in the range of 0 °C to 40 °C. In order to ensure well soaking of the paint and to avoid drying, the cleaner should be continuously distributed over the painted surface by brushing. The recommended application rate is appr. 400 g/m². If necessary, additional amounts of the cleaner can also be applied later on. After an exposure time of 15 - 30 minutes paint residues should be washed away by use of a high-pressure cleaner (max. 12 bar). Exposure times of more than 30 minutes are not recommended. It is necessary to ensure that the protective layer does not get damaged by high water pressure or too much mechanical stress. The described cleaning procedure should be carried out twice. Painted and lacquered surfaces, such as window frames or metal pieces, might be damaged by contact with the cleaner. It is always recommended to conduct test patches in order to avoid unwanted side effects. Shake well before use.



This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Europe / Middle-East / Africa

Evonik Operations GmbH

Silanes Business Line
Rodenbacher Chaussee 4
63457 Hanau-Wolfgang
Germany
FAX +49 6181 59 713 915
protectosil@evonik.com
www.protectosil.com

Asia / Pacific

Evonik (SEA) Pte. Ltd.

Silanes Business Line
3 Internatioanl Business Park
#07-18, Nordic European Centre
Singapore 609927
PHONE +65 6809 6906
FAX +65 6809 6699
protectosil@evonik.com
www.protectosil.com

Asia / Pacific

Evonik Taiwan Ltd.

Silanes Business Line
Artist Construction Bldg
9F, No. 133
Min Sheng East Road, Sec 3
Taipei, 105 Taiwan, R.O.C.
Taiwan 10596
PHONE +886 227 17 1242 #247
FAX +886 227 17 2106
protectosil@evonik.com
www.protectosil.com

North America

Evonik Corporation

Silanes Business Line
299 Jefferson Road
Parsippany, NJ 07054
USA
PHONE (TOLL FREE) +1 800 828 0919
protectosil@evonik.com
www.protectosil.com

Asia / Pacific

Evonik (Shanghai) Co. Ltd.

Silanes Business Line
55, Chungdong Road
Shanghai 201108
P.R. China
PHONE +86 21 6119 1660
FAX +86 21 6119 1075
protectosil@evonik.com
www.protectosil.com

Asia / Pacific

Evonik Japan Co. Ltd

Silanes Business Line
12th Floor Monolith Building
2-3-1, Nishi-Shinjuku-ku
Tokyo 163-0912
Japan
PHONE +81 353 23 7446
FAX +81 353 23 7397
protectosil@evonik.com
www.protectosil.com

Region Central and South America

Evonik Brasil Ltda.

Silanes Business Line
Rua Arquiteto Olavo Redig de Campos, 105
Torre A - 04711-904 São Paulo- SP
Brazil
PHONE +55 11 3146 9627
protectosil@evonik.com
www.protectosil.com

Asia / Pacific

Evonik Korea Ltd.

Silanes Business Line
3F (Nongshim Sungmookwan B/D)
112 Yeouidaebang-Ro
Dongjak-Gu
Seoul, 07057
Korea
PHONE +82 2320 4778
FAX +82 2783 2520
protectosil@evonik.com
www.protectosil.com

Asia / Pacific

Evonik India Pvt. Ltd.

Silanes Business Line
Krislon House
Saki Vihar Road, Anderi (E)
Mumbai - 400 072
India
PHONE +91 226 7238 809
FAX +91 226 7238 811
protectosil@evonik.com
www.protectosil.com