

VPS SIVO 260

Modified organofunctional silane oligomer

Technical data

Properties and test methods	Value	Unit	Method
Density (20 °C)	approx. 1.15	g/cm ³	DIN 51757
Flash point	> 95	°C	EN 22719
Viscosity (20 °C)	<= 750	mPa's	DIN 53019
Physical form	colorless to light yellowish	-	-

Registrations

VPS SIVO 260

EINECS/ELINCS (EU):	Yes
AICS (Australia):	*
DSL/NDSL (Canada):	*
PICCS (Philippines):	*
TSCA (USA):	*
IECSC (P.R. China):	*
ENCS (Japan):	*
ECL (South Korea):	*
REACH (Europe)	Exempted
* = information upon request	

VPS SIVO 260 is a novel multifunctional siloxane adhesion promoter with aminofunctionalities that can be used for various applications.

VPS SIVO 260 is mainly dedicated for use in adhesives & sealants to improve the adhesion of hybrid products (e.g. silylated polyurethanes, MS Polymers®) and RTV-silicones - especially to difficult to stick polycarbonate substrates. In addition, VPS SIVO 260 can lead to adequate adhesive cure and it imparts both additional flexibility and hydrophobicity.

Properties and applications

VPS SIVO 260 is a versatile product that provides improved product performance and quality. VPS SIVO 260 is soluble in alcohols, aliphatic and aromatic hydrocarbons, but it can undergo reactions with ketones or ester solvents. VPS SIVO 260 is considered primarily as an additive in moisture curable adhesives & sealants to eliminate the need for special primers in numerous bonding applications. Loading levels of 0,5 to 2,0 wt. % of VPS SIVO 260 as an additive - calculated on the overall formulation - are typically recommended.

Our recommendation:

VPS SIVO 260 has been developed mainly for use in:

- MS Polymer®
- Silane modified polyurethane/ polyether
- RTV-1/RTV-2 silicones
- Butyl rubber

We do not recommend to use VPS SIVO 260 in 1K-PU or 1K-EP formulations. The compatibility of other ingredients with VPS SIVO 260 should be tested in advance.

Key Benefits

VPS SIVO 260 exhibits excellent wetting on substrates and it can form weather- and moisture-resistant bonds to substrates which are partially difficult to adhere. The main benefits of VPS SIVO 260 in silylated polyurethane or MS polymer based adhesives & sealants are:

- Improved adhesion to plastics, especially to polycarbonate
- Improved adhesion to aluminum
- Well-Balanced mechanical properties
- Significant VOC-reduction compared to conventional amino silanes

Safety and handling

Before considering the use of VPS SIVO 260 please read its Safety Data sheet (SDS) thoroughly for safety and toxicological data as well as for information on proper transportation, storage and use. The Safety Data Sheet is available after registration on our website www.dynasytan.com or upon request from your local representative, customer service or from Evonik Resource Efficiency GmbH, Product Safety Department, E-MAIL sds-hu@evonik.com.

Packaging, storage and shelf life

VPS SIVO 260 is available in 25 kg pails, 200 kg drums and 1.000 kg IBC's.

The shelf life of VPS SIVO 260 is min. 9 months from delivery.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Europe/Middle-East/Africa/RoW
Evonik Resource Efficiency GmbH

Business Line Silanes
Rodenbacher Chaussee 4
63457 Hanau-Wolfgang
Germany
PHONE +49 6181 59 13636
FAX +49 6181 59 713915
dynasytan@evonik.com
www.dynasytan.com

Asia / Pacific

Evonik (SEA) Pte. Ltd.

Business Line Silanes
3 Internatioanl Business Park
#07-18, Nordic European Centre
Singapore 609927
PHONE +65 6809 6576
FAX +65 6809 6699
dynasytan@evonik.com
www.dynasytan.com

Asia / Pacific

Evonik Japan Co. Ltd

Business Line Silanes
12th Floor Monolith Building
2-3-1, Nishi-Shinjuku-ku
Tokyo 163-0912
Japan
PHONE +81 353 23 7446
FAX +81 353 23 7397
dynasytan@evonik.com
www.dynasytan.com

North America

Evonik Corporation

Business Line Silanes
299 Jefferson Road
Parsippany, NJ 07054-0677
USA
PHONE (TOLL FREE) +1 800 237 67 45
PHONE +1 973 929 8513
FAX +1 973 929 8503
dynasytan@evonik.com
www.dynasytan.com

Asia / Pacific

Evonik Specialty

Chemicals (Shanghai) Co. Ltd.

Business Line Silanes
55, Chungdong Road
Xinzhuang Industry Park
Shanghai 201108
P.R. China
PHONE +86 21 61191-399
FAX +86 21 61191-648
dynasytan@evonik.com
www.dynasytan.com

Asia / Pacific

Evonik India Pvt. Ltd.

Business Line Silanes
Krislon House
Saki Vihar Road, Anderi (E)
Mumbai - 400 072
India
PHONE +91 226 7238 809
FAX +91 226 7238 811
dynasytan@evonik.com
www.dynasytan.com

North America

Silbond Corporation

9901 Sand Creek Highway
Weston, MI 49289
USA
PHONE +1 517 436 9316
FAX +1 517 436 3148
dynasytan@evonik.com
www.dynasytan.com

Asia / Pacific

Evonik Korea Ltd.

Business Line Silanes
94, Galsan 1-dong
Bupyeong-gu
Incheon, 403-081
Korea
PHONE +82 2320 4773
FAX +82 2783 2520
dynasytan@evonik.com
www.dynasytan.com

Latin America

Evonik Brasil Ltda.

Business Line Silanes
Alameda Campinas, 579
01404-000 São Paulo-SP
Brazil
PHONE +55 11 3146 4123
FAX +55 11 3146 4148
dynasytan@evonik.com
www.dynasytan.com

Asia / Pacific

Evonik Taiwan Ltd.

Business Line Silanes
Artist Construction Bldg.
9F, No. 133
Min Sheng East Road, Sec 3
Taipei, 105 Taiwan, R.O.C.
Taiwan 10596
PHONE +886 227 17 1242
FAX +886 227 17 2106
dynasytan@evonik.com
www.dynasytan.com