

# ZEOLEX® 330

## Precipitated Sodium Alumino Silicate

### Characteristic physico-chemical data\*

Properties and test methods	Unit	Value
Median particle size	µm	6
Linseed oil absorption	ml/100g	130
pH value, 20 % in water	-	10
Specific Gravity	g/cm <sup>3</sup>	2.0
BET Surface Area	m <sup>2</sup> /g	80

\*) The given data are typical values. Specifications on request.

### Certifications and Classifications

#### ZEOLEX® 330

CAS-No.	1344-00-9
<ul style="list-style-type: none"> <li>Consistent quality excellence achieved through effective process control, an ISO:9001 registered quality management system and implemented GMPs</li> </ul>	

ZEOLEX® 330 Sodium Alumino Silicate powder is used in paints and coatings applications as a titanium dioxide (TiO<sub>2</sub>) extender and gloss sheen control agent. ZEOLEX® 330 Sodium Alumino Silicate has the whitest and brightest properties of the Evonik ZEOLEX® family. ZEOLEX® 330 Sodium Alumino Silicate provides excellent opacity, whiteness, brightness, flattening and scrub resistance for interior architectural formulations. ZEOLEX® 330 Sodium Alumino Silicate pigment is used as an extender for titanium dioxide on both sides of CPVC. Below CPVC, the small particles of 0.1 to 0.5 microns work as spacer/extenders for titanium dioxide. Above CPVC, the structure based on the particle size building blocks functions as an effective light scattering material in the paint to increase opacity or to compensate for a reduced titanium dioxide content.

### Benefits

- Improved scrub resistance
- Superior performance in flattening
- Improved matting
- Reduced TiO<sub>2</sub> loading by up to 25%
- Equally effective in solvent born and water born systems
- Delivers cost savings
- Particle distribution is optimized for packing in the film
- Excellent touch up performance

### Safety and Handling

Information concerning the safety of this product is listed in the corresponding Safety Data Sheet. We recommend to read carefully the Safety Data Sheet prior to the use of our product.

### Packaging and storage

For details regarding our packaging options for this product, please contact your local sales representative.

Our silica products are inert and extremely stable chemically. However, due to their high specific surface area, they can absorb moisture and volatile organic compounds from the surrounding atmosphere. Therefore, we recommend storing the products in sealed containers in a dry, cool place, and removed from volatile organic substances. Even if a product is stored under these conditions, after a longer period it can still pick up ambient moisture over time, which could lead to its exceeding the specified moisture content.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

**Applied Technology****Evonik Resource Efficiency GmbH**

Business Line Silica  
Rodenbacher Chaussee 4  
63457 Hanau-Wolfgang  
Germany  
PHONE +49 6181 59-3536  
FAX +49 6181 59-4096  
ask-si@evonik.com  
www.sipernat.com

**Europe/ Middle-East/****Africa/ Latin America****Evonik Resource Efficiency GmbH**

Business Line Silica  
Rodenbacher Chaussee 4  
63457 Hanau-Wolfgang  
Germany  
PHONE +49 6181 59-8118  
FAX +49 6181 59-78118  
ask-si@evonik.com  
www.sipernat.com

**North America****Evonik Corporation**

Business Line Silica  
299 Jefferson Road  
Parsippany, NJ 07054-0677  
USA  
PHONE +1 800 233-8052  
FAX +1 973 929-8502  
ask-si@evonik.com  
www.sipernat.com

**Asia-Pacific****Evonik (SEA) Pte. Ltd.**

Business Line Silica  
3 International Business Park  
#07-18, Nordic European Centre  
Singapore 609927  
PHONE +65 6 809 6877  
FAX +65 6 809 6677  
ask-si-asia@evonik.com  
www.sipernat.com